

## AES-SP1X2

The Whirlwind AES Splitter 1x2 is a passive unit that delivers two identical AES/EBU signals from a single stream. The design utilizes a dual secondary transformer on the input and a separate isolation transformer for each output. With the three-transformer circuit, the Whirlwind AES-SP1X2 maintains excellent data integrity and high amounts of isolation between outputs.

Sample Rates 32 - 192 kHz

Fast Rise time, Low Capacitance

Low Jitter

Low pulse aberration

Gold plated XLR female input to 2 gold plated male XLR outputs



**whirlwind**®

[www.whirlwindusa.com](http://www.whirlwindusa.com)



Made In USA

The AES-SP1X2 is also available as a four channel rack mount unit, model number AES-MLTSP1X2. This 1RU enclosure contains four of the single 1X2 AES circuits. All connections are on the rear of the unit.

This product is warranted to be free of defects in materials or workmanship to the original purchaser for a period of 3 years from the date of purchase. Should warranty service be required, return the unit postage paid along with the original sales receipt to:

Whirlwind Music Dist., Inc.  
99 Ling Road  
Rochester NY 14612

Whirlwind will, at its option, repair or replace the unit. This warranty does not cover damage resulting from abuse, unauthorized modifications or use of the product in unintended applications.



[www.whirlwindusa.com](http://www.whirlwindusa.com)